

ZEROALPHA

SOLUTIONS

DEPLOY LIGHTER **LAST LONGER**

4 Port High-Capacity USB Adaptor **90

Robust and lightweight support to tactical energy

The ZeroAlpha high-capacity USB adaptor enables users to extract energy from their in-service **90 batteries and allow them to quickly charge in-service USB systems at a maximum of 3A per USB port.

Legacy **90 USB adaptors have struggled to keep up with the higher charging demands of modern USB 3.0 devices resulting in slower charging times and increased delays in turning equipment round in remote and austere environments.

Built to operate in the harshest of environments these units are made from robust aluminium and powder coated to ensure they stand the test of time and deliver a long-term return of investment.

Part Number: ZAS-PM-280
NSSN: 6138-99-847-8691



Silent Power



Plug and Play



Reduced Emissions



Robust design



Input Voltage:	20-38VDC
Output Voltage:	5VDC up to 3 Amps maximum per port
Protocol Support:	QC3.0, QC2.0 (Android and iOS) Input over voltage, under voltage protection Input over current protection Output over current and short circuit protection Over temperature protection
Outside Dimensions:	2.6" X 4.5" X 1.4"
Weight:	10.58 Ounces
Material:	Aluminum Epoxy powder coating, extremely durable
Temperature:	-40C to +85C
Compatibility:	BB-390, BB-490, BB-2590, BB-590, BB-7590 BA-5590



Designed in the UK



Warranty and Service

info@zeroalphasolutions.com

www.zeroalphasolutions.com

Images are for illustrative purposes only and actual products and examples may differ from those shown. All details correct at time of going to press but subject to change. E & EO.

